Sitron

Ordering Information

MODEL

- CN1DC
- CN1DCRF
- CN2DC
- CN2DCRF
- CN1AC
- CN1ACRF
- CN2AC
- CN2ACRF

SIZE

- 0 NONE
- 3 ½”
- 4 3/4”
- 5 1”
- 6 1 ½”
- 7 2”
- 8 2 1/2”
- 9 3”
- A 1 1/4”
- B M30(E)
- Q 4”
- X OTHER

PROCESS CONNECTION TYPE

- B BSP
- D FLANGE ANSI 150# CARBON STEEL PAINTED
- E FLANGE ANSI 150# 316 SS
- F FLANGE ANSI 150# - PVC
- M METRIC THREAD
- K FLANGE ANSI 150# - 304 SS
- N NPT
- R SMS FEMALE
- S SMS MALE
- T TRI CLAMP
- U NK25
- Y FEMALE DIN 316SS
- X OTHER SPECIFY

TYPE OF ROD OR CABLE

- O NONE
- A FIXED ROD 1/4” - 316 SS
- L REMOVABLE ROD 1/4” - 316 SS
- N PVC CABLE
- S SILICON CABLE 2.5mm
- U REFERENCE CABLE 5/32” - 316 SS
- X OTHER

COATING/ TUBING

- S NONE
- E EPOXY (up to 120°C)
- H COATED HALLAR (up to 150°C)
- N NYLON
- P PEEK (up to 260° C)
- X OTHER SPECIFY

INSERTION LENGTH

- L SPECIFY

HOUSING

- N1 SMALL NYLON
- G1 SMALL ALUMINUM

ELECTRICAL CONNECTION

- 1 ½" BSP (N1 OR G1)
- 2 CABLE GLAND W/ 1/2" BSP
- 3 3/4" BSP (G1)
- 5 CABLE GLAND W/ 3/4" BSP (G1)
- 6 ½" NPT (N1 OR G1)
- 7 CABLE GLAND W/ 1/2" NPT
- 8 1/2"NPT CABLE GLAND & 2m CABLE
- 9 3/4" NPT (G1)
- C CLIMPED W/ 2m OF CABLE (EL - SC)
- Y CABLE GLAND W/ M16 METAL (A1)

OPTIONS

- O NONE
- A CLAMP
- E SINGLE ELECTRODE IN A POLIPROPELENE ENCLOSURE
- F O'RING VITON OR TEFLON
- L ADAPTOR
- MT MEDIUM TEMPERATURE - 50mm 316 SS NECK (80-120°C)
- AT HIGHT TEMPERATURE - 100mm 316 SS NECK (80-150°C)
- N NIPPLE FOR NK25 (½"BSP)
- S SANITARY NIPPLE

CN