

Ordering Information

MODEL	
SC400	
SIZE	
4	3/4"
5	1"
6	1 1/2"
7	2"
9	3"
Q	4"
X	OTHER
PROCESS CONNECTION TYPE	
B	BSP
D	FLANGE ANSI 150# CARBON STEEL PAINTED
E	FLANGE ANSI 150# 316 SS
G	FLANGE ANSI 300# CARBON STEEL PAINTED
H	FLANGE ANSI 300# 316 SS
K	FLANGE ANSI 150# - 304 SS
L	FLANGE ANSI 300# - 304 SS
N	NPT
S	SAE O'RING - 316SS
T	TRI CLAMP
X	OTHER SPECIFY
TYPE OF ROD	
C	ROD & SHEATH 316SS 1/2"(12,7mm)
R	ROD - 316SS 1/2"(12,7mm)
IA	INACTIVE + ACTIVE
COATING	
S	NONE
E	EPOXY (up to 120°C)
H	COATED HALLAR (up to 150°C)
M	COATED PTFE (up to 260°C)
P	PEEK (up to 260° C)
T	PTFE TUBED
X	OTHER - SPECIFY
INSERTION LENGTH	
L	SPECIFY
HOUSING	
N1	SMALL NYLON
G1	SMALL ALUMINIUM
ELECTRICAL CONNECTION	
1	1/2" BSP
2	CABLE GLAND W/ 1/2" BSP
4	3/4" BSP
5	CABLE GLAND W/ 3/4" BSP
6	1/2" NPT
7	CABLE GLAND W/ 1/2" NPT
9	3/4" NPT
C	CABLE GLAND W/ 3/4" NPT
OPTIONS	
MT	Medium Temp - 50mm 316SS Neck (80-120°C)
AT	High Temp - 100mm 316SS Neck (80-150°C)
HT	Highest Temp - 100mm + Coil 316SS Neck (80- 200°C)
ST	316SS Tag
SC400	

MODEL	
LV400/2-24	Power Supply: 24Vcc (+/- 10%) - Out: 1NO + 1NC
LV400/2-11	Power Supply: 110Vca (50/60Hz) - Out: 1NO + 1NC
LV400/2-23	Power Supply: 230Vca (50/60Hz) - Out: 1NO + 1NC

